



Third West Air Monitor Result Shepherd, Michael

Joyce Ackerman, 'Craig Barnitz (cbarnitz@utah.gov)' 03/16/2012 09:27 AM

Hide Details

From: "Shepherd, Michael" < Michael. Shepherd @PacifiCorp.com>

To: Joyce Ackerman/R8/USEPA/US@EPA, "Craig Barnitz (cbarnitz@utah.gov)" <cbarnitz@utah.gov>

1 Attachment



Joyce & Craig,

We had five positive hits on Tuesday, March 13, 2012. All were chrysotile, see the attached. Again, I strongly believe this is due to very windy and dry conditions we are having. The crew has been very good to wet down our site, but we can't control what is coming off the roofs of the older buildings around our site. It is supposed to rain this weekend, that should help! Please let me know if you have any questions or concerns.

Thanks,

Mike Shepherd
Project Manager
Rocky Mountain Power - Major Projects
801.220.4584 Office
801.631.1310 Cell
801.220.2797 Fax
michael.shepherd@pacificorp.com



March 15, 2012

Laboratory Code: Subcontract Number:

RES NA

Laboratory Report: Project # / P.O. #

RES 231640-1 None Given

Project Description:

3rd West Sub - RMP

Eldon Romney R & R Environmental 47 West 9000 South #2 Sandy UT 84070

Dear Customer,

Reservoirs Environmental, Inc. is an analytical laboratory accredited for the analysis of Industrial Hygiene and Environmental matrices by the National Voluntary Laboratory Accreditation Program (NVLAP), Lab Code 101896-0 for Transmission Electron Microscopy (TEM) and Polarized Light Microscopy (PLM) analysis and the American Industrial Hygiene Association (AIHA), Lab ID 101533 - Accreditation Certificate #480 for Phase Contrast Microscopy (PCM) analysis. This laboratory is currently proficient in both Proficiency Testing and PAT programs respectively.

Reservoirs Environmental, Inc. has analyzed the following samples for asbestos content as per your request. The analysis has been completed in general accordance with the appropriate methodology as stated in the attached analysis table. The results have been submitted to your office.

RES 231640-1 is the job number assigned to this study. This report is considered highly confidential and the sole property of the customer. Reservoirs Environmental, Inc. will not discuss any part of this study with personnel other than those of the client. The results described in this report only apply to the samples analyzed. This report must not be used to claim endorsement of products or analytical results by NVLAP or any agency of the U.S. Government. This report shall not be reproduced except in full, without written approval from Reservoirs Environmental, Inc. Samples will be disposed of after sixty days unless longer storage is requested. If you have any questions about this report, please feel free to call 303-964-1986.

Sincerely,

Jeanne Spencer Orr

President

RESERVOIRS ENVIRONMENTAL, INC.

NVLAP Lab Code 101896-0; TDH: #30-0015

TABLE I. TEM AIR FILTER SAMPLE DATA AND ANALYTICAL RESULTS

RES Job Number:

RES 231640-1

Client:

R & R Environmental

Client Project Number / P.O.: Client Project Description:

None Given

Date Samples Received:

3rd West Sub - RMP

Analysis Type:

March 14, 2012

TEM, AHERA

Turnaround:

24 Hour

Date Samples Analyzed:

March 14, 2012

Client	Lab		Area	Air	Number of	Analytical	Asbestos	Filter
ID Number	ID Ni	umber	Analyzed	Volume · Sampled	Asbestos Structures Detected	Sensitivity	Concentration	Loading
			(mm²)	(L)		(s/cc)	(s/cc)	(s/mm ²)
3W-031312 W	EM	872644	0.0900	936	ND	0.0046	BAS	BAS
3W-031312 N	EM	872645	0.0900	936	3	0.0046	0.0137	33.3
3W-031312 E	EM	872646	0.0900	936	ND	0.0046	BAS	BAS
3W-031312 S	EM	872647	0.0900	936	2	0 0046	0.0091	22.2

NA = Not Analyzed

ND = None Detected

BAS = Below Analytical Sensitivity

Average Grid Opening in mm² = 0.010

Filter Material = Mixed Cellulose Ester

Filter Diameter = 25 mm

Effective Filter Area = 385 sq mm

DATA QA

RESERVOIRS ENVIRONMENTAL, INC.

NVLAP Lab Code 101896-0; TDH: #30-0015

TABLE II. SUMMARY OF ANALYTICAL DATA

RES Job Number:

RES 231640-1

Client:

R & R Environmental

Client Project Number / P.O.:

None Given

Client Project Description:

Date Samples Received:

3rd West Sub - RMP

March 14, 2012

Analysis Type:

TEM, AHERA

Turnaround:

24 Hour

Date Samples Analyzed:

March 14, 2012

Client ID Number	Lab A D Number		Asbestos Mineral	Asbestos Structure Types*				Structures >5 Microns in Length	**Excluded Structures	Asbestos Structures for	
•			_	Fibers	Bundles	Clusters	Matrices	•		Concentration	
3W-031312 W	EM	872644	ND	0	0	0	0	0	0	0	
3W-031312 N	EM	872645	Chrysotile	1	2	0	0	1	0	3	
3W-031312 E	EM	872646	ND	0	. 0	0	0	0	0	0	
3W-031312 S	EM	872647	Chrysotile	2	0	0	0	0	0	2	

^{*}See Analytical Procedure for definitions

^{**}C = Excluded from total due to lack of confirmation

^{**}L = Excluded from total for length less than 0.5 micron (AHERA only)

^{**}A = Excluded from total due to i ncorrect aspect ratio

ND = None Detected

Due Date: 31512

Reservoirs Environmental, inc.

5801 Logan St. Denver, CO 80216 • Ph; 303 864-1986 • Fax 303-477-4275 • Toll Free :866 RESHENV Pager: 303-509-2098 INVOICE TO: (IF DIFFERENT) **CONTACT INFORMATION:** Company: 12 12 Environmental Company: Contact () and Roskelles Address: nono: 47 W 90000 #2 Faxt Sundy, Ut. 84070 Cell/pager: 801 541-1035 Coll/pager. Project Number add/br P.O. #: dove @ menio com Project Description/Leedson: 3 = West Sub - RMP REQUESTED ANALYSIS ASBESTOS LABORATORY HOURS: Weekdays: 7am - 7pm VALID MATRIX CODES LAB NOTES: PLM / PCM / TEM RUSH (Same Day) PRIORITY (Next Day) STANDARD Air = A Bulk = B (Rush PCM = 2hr, TEM = 6hr.) Dust = D Paint = P CHEMISTRY LABORATORY HOURS: Weekdays: Sam - Spm Soil = S Wipe = W Metal(s) / Dust __RUSH ____ 24 hr. ___ 3-5 Day Swab = SW F = Food "Prior notification is RCRA 8 / Metals & Welding Drinking Water = DW Waste Water = WW _RUSH ____ 5 day ____10 day required for RUSH Point Count Fume Scan / TCLP O = Other ISO, +/-, rect Preps turnarounds.** Organics 24 hr. ___ 3 cay __ SOay "ASTM E1792 approved wipo modia only" MICROBIOLOGY LABORATORY HOURS: Weekdays: Sam - 6pm Ecoli Q157:H7, Coliforms, Saureus ____ 24 hr. ____2 Day ___3-5 Day Salmonella, Listeria, E.coli, APC, Y & M ____ 48 Hr. ___3-5 Day Long Mold RUSH ___ 24 Hr ___ 46 Hr ___ S Day ___ S Day Turnaround limes establish a laboratory priority, subject to laboratory volume and any not guarantocd. Additional foes nppty for afternours, weekends and holidays." Special Instructions: EM Number (Laboratory Date Time Use Only) Collected Collected Client sample ID number (Sample ID's must be unique) mm/dd/yy hh/mm n/o × 311317 936 3W-031312 F 936 3W-03i3 8 10 Number of samples received: (Additional samples shall be listed on attached long form.) NOTE: REI will finally a incoming samples based upon information received and will not be responsible for errors or amissions in cold/stations resulting from the inaccuracy of original data. By signing client/company representative agrees that submission of the following samples for requested analysis as indicated on this Chain of Custody shall constitute an analytical services agracinent with payment tenns of NET 30 days, failure to comply with payment terms may result in a 1.5% monthly interest curcharge. Relingulshed By: Sample Condition: Date/Time: On loe Sealed Intact Laboratory Use Only Yes/No Temp. (F°) Yes / No Yas / No Date/Time: Received By: Results: Contact Dane Date 3/1 Time 2: 450 Initials. Phone, Email Fax Date Time Initials Contact Phone Email Fax Time Contact Phone Email Fax Oate Time Initials 7933 2999 4944

7-2011_version 1

Attachment I

Key to Count Sheets Count Sheets Analytical Procedures

Structures identifications consist of an Asbestos Type followed by a Structure Type

Asbestos Type

Structure Types

A = Amosite	F = Fiber
An = Anthophyllite	B = Bundle
C = Chrysotile	C = Cluster
Cr = Crocidolite	M = Matrix
T = Tremolite	

ND = no structures detected

M = other structure associated with a matrix

NAM = Non Asbestos Mineral

XGB = partly obscured by a grid bar


Sizing Conversion

1 length unit = 5 mm on screen = 0.278 micron
1.80 length units = 0.5 micron
18.0 length units = 5 microns

1 width unit = 1 mm on screen = 0.0556 micron

TEM Analysts

Jeanne S. Orr Nathan DelHierro Angela Heitger Jonathan Bernard Paul D. LoScalzo Mark Steiner Norberto Zimbleman Robert Workman



Upper and lower 95% confidence bounds for the number of structures counted assuming a Poisson distribution.

Reservoirs Environmental, Inc. TEM Asbestos Structure Count

Laboratory name:	·加州市公司(南部城市) · · · · · · · · · · · · · · · · · · ·
Instrument	JEOL 100 CX N S
Voltage (KV)	100 KV
Magnification	(20KX) 10KX
Grid opening area (mm2)	0.010
Scale: 1L=	0.28 um
Scale: 10 =	0.56 um
Primary filter area (mm2)	385
Secondary Filter Area (mm2)	
ОА Туре	

Client :	
Sample Type (A=Air, D=Dust):	15-44-15-16-16
Air volume (L) or dust area (cm2)	1980
Oate received by lab	TEMPOPOLICE IN THE PROPERTY OF
Lab Job Number:	ME STAR BE
Lab Sample Number:	194721844

F-Factor Calculation (Indirect Preps	Only):	
Fraction of primary filter used		
Total Resuspension Volume (ml)		
Volunte Applied to secondary filter (ml)		

Analyzed by	MC
Analysis date	3/14/12
Method (D=Oirect, I=Indirect, IA=Indirect, IA=Indirect, ashed)	想力を対
Counting rules (ISO, ANERA, ASTM)	AL
Grid storage location	Month Analyzed
Scope Alignment	Date Analyzed

Grid	Grid Opening	Structure	No. of St	ructures	Dimensions		Identification	Mineral Class					1 = yes, blank = no		
Gild	Ond Opening	Туре	Primary	Total	Length	Width	identinoadon	Amphibole	C:	NAM	Sketch/Comments	Sketch	Photo	EDS	
A	K5-6	M													
	H5-6	M			22	of A	90/ Wa	cx 5-7)	del	in					
	[15-6	in			ln	ese B	M:	1 - fin	3/17	1/2					
	F5-6	M				1 /			6.						
	25-6	M			<u> </u>										
3	F6-1	M								<u> </u>					
	H6-1	M								,					
	96-1	·M													
	16-1	MD													

Reservoirs Environmental, Inc. TEM Asbestos Structure Count

Laboratory name:	THE MAN
Instrument	JEOU 100 CX. N. S.
Voltage (KV)	100 KV
Magnification	20KX) 10KX
Grid opening area (mm2)	7. E. O. 010 F. O. 0
Scale: 1L=	0.2S um
Scale: 1D =	是20.56 um 》上
Primary filter area (mm2)	385112666
Secondary Filter Area (mm2)	
QA Tvoe	THE PLANT

建酸水溶酶
122 Tales
1777.2645

F-Factor Calculation (Indirect Pro	eps Onty):
Fraction of primary filter used	
Total Resuspension Volume (mf)	
Volume Applied to secondary filter (ml)	

Analyzed by	- M
Analysis date	3/14/12
Method (D≂Oirect, l=Indirect, IA≃Indirect, ashed)	THE DEVE
Counting rules (ISO, AHERA, ASTM)	2A4
Grid storage location	Month Analyzed
Scope Alignment	Date Analyzed

Grid	Grid Opening	Structure	No. of St	ructures	Dime	nsions	Identification	Mineral Class		1=		ves, blank = no		
U	Gild Opening	Туре	Primaly	Total	Length	Width	Identinoation	Amphibole	ပ	NAM	Sketch/Comments	Sketch	Photo	EDS
A	64-3	B		1.	23	10	cn		-سر ٠	 				
		B		2	5	3	cn_	•			R			
				3	2	j	css.		/					
	F4-3	30												
	24-3	M			Qn	r A	907.14	10-Ch-5-7	de	bres				
	· 14-3	NP		,		-								
	134-3	W												
B	64-6	W			1									
	fu-6.	M												
	24-6	M					}					1		

<u>~</u> o	f	۷
	<u>~</u> of	<u>∠</u> of

Reservoirs Environmental, Inc. TEM Asbestos Structure Count

LAB NAME	REI	Lab Job Numben	231640	Analyzed by:	LK
		Lab Sample Number	972645	Analysis Date:	3/14/12

Grid	Grid	Structure	No. of Str	uctures	Dime	nsions	Identification	Min	Mineral Class			1 = y	1 = yes, blank = no	
	Opening	Туре	Primary	Total	Length	Width		Amphibole	С	NAM	Sketcly/Comments	Sketch	Photo	EDS
	04-6	M								·				
						Prier	B80(Macin	ジーチ	Toles	3 July	3/14	112	
						_								
							·							
					·				ı					
		·												
				·			·							
				Ţ					J					

Reservoirs Environmental, Inc. TEM Asbestos Structure Count

Laboratory name:	REI PALL
Instrument	JEOL 100 CX N S
Voltage (KV)	100 KV
Magnification	= (20KX) 10KX
Grid opening area (mm2)	E 37 0.010 X 3
Scale: 1L =	0.28 iin
Scale: 1D =	0.56 um
Primary filter area (mm2)	385
Secondary Filter Area (mm2)	当的特殊的思想
QA Туре	

	Na Daniel Submissi
Client:	13年10月25日三年11年1
Sample Type (A=Air, D=Dust):	
Air volume (L) or dust area (cm2)	
Date received by lab	增加弹助理
Lab Job Number	PERMITO
Lab Sample Number:	13012516
Can Carriero (Carriero).	I seld his war has so the last

Lab Sample Number:	LANCHARD COLUMN
F-Factor Calculation (Indirect F	reps Only):
Fraction of primary fittar used	
Total Resuspension Volume (ml)	
Volume Applied to secondary filter (ml)	

Analyzed by	M
Analysis date	3/14/12
Method (D=Direct, I=Indirect, IA=Indirect, ashed)	and D
Counting rules (ISO, AHERA, ASTM)	2A4
Grid storage location	Month Analyzed
Scope Alignment	Date Analyzed

Grid	Grid Opening	Structure	No. of St	ructures	Dime	nsions	Identification	Mineral Class				1 = y	es, blank	= no
O,110	Ond Opening	Туре	Primary	Total	Length	Width	identification	Amphibole	С	NAM	Sketch/Comments	Skelch	Photo	EDS
 4	64-6	M).									,	•		
	FULG	M			R	nex l	857 1	via C+3-7	7 de	bini		٠.		
	ent	M		,	. f	ner 1	2-14.	Mac+3-7	3/14	1/12		<u> </u>		
·	C4-6	M							<u> </u>					
	316	M			<u> </u>		<u> </u>							
<u>ه</u> .	H3-1	M		·										
	921	M					<u> </u>							l
	F3-1	M												
	9.3-1	M).							·					
							,							

Reservoirs Environmental, Inc. TEM Astrestos Structure Count

Laboratory name:	THE REISON
Instmment	JEOL 100 CX 11 S
Voltage (KV)	100 KV
Magnifiaation	(20KX) 10KX
Grid opening area (mm2)	0.0105
Scale: 1L=	0.28 um
Scale: 1D =	0.56 um
Primary filter area (mm2)	385 12 18
Secondary Filter Area (mm2)	
QA Tvoe	

Client:	THE SECRET
Sample Type (A=Air, D=Dust):	THE PARTY NAMED IN
Air volume (L) or dust area (om2)	連續認為
Date received by lab	阿爾斯爾
Lab Job Numben	
Lab Sample Number:	新国 区4年

Analyzed by	- M
Analysis date	3/14/12
Method (D=Oirect, (=Indirect, IA=Indirect, ashed)	清·D·
Counting rules (ISO, AHERA, ASTM)	-A1
Grid storage location	Month Analyzed
Scope Alignment	Date Analyzed
•	•

F-Factor Calculation (Indirect Pre	ps Only):
Fraction of primary finer used	
Total Resuspension Volume (ml)	
Volume Applied to secondary filter (ml)	

Grid	Grid Opening	Structure Type	No. of Structures		Dimensions		Identification	Mineral Class			1 = yes, blank = no			
			Primary	Total	Length	Width	Identification	Amphilxale	Ċ	NAM	Sketoh/Commients	Sketch	Photo	EDS
A	K5-3	M										-		•
	H5-3	NO					<u> </u>	•						
	as:3	(M.		,						1				
	F3-3	F		(2.5	2_	Cry .				/			
	95-3	M				ln	x A 908	wiew-5-	720	leb ñ	3			
0	K6-4	F		2	3:5	. 1	Co				/	•		
	Hoy	NO		,		Pn	m Barj		V	2/1	4/12			
	96-4	M				_				7				
	P6-4.	W.							·			T .		
									1			·		

Analytical Procedures - AHERA

Transmission electron microscopy/energy dispersive X-ray spectrometry/selected area electron diffraction (TEM/EDX/SAED) was employed in the analysis of the samples, which were collected on 25 mm mixed cellulose ester air filters. A portion of each filter was collapsed with acetone and etched in a plasma asher. The etched filter was then coated with a thin layer of carbon in a carbon side down. The sample was then placed inside a condensation washer and treated with acetone to remove the filter matrix and expose any inert material.

For each sample, enough grid openings on a 200 mesh TEM grid are analyzed to ensure an analytical sensitivity of at least 0.005 structures/cc. A minimum of four grid openings from two preparations are analyzed for each sample. The grid openings are searched for fibrous structures which, if present are analyzed by SAED and/or EDX (elemental analysis). The AHERA protocol requires SAED confirmation of enough chrysotile asbestos structures on each sample to cause the sample to exceed 70 structures/mm² (usually 4 or 5 structures). Both SAED and EDX confirmation are required of enough amphibole structures on each sample to cause the sample to exceed 70 structures/mm² (usually 4 or 5 structures) per sample. Either SAED or EDX is required for the remaining asbestos structures of either type. The morphology of each structure is determined and the length and the diameter of any asbestos structures are recorded. Asbestos fibers, bundles, cluster and matrices were identified and recorded. The asbestos structures have been defined in AHERA as follows:

Fiber: is a structure having a minimum length greater than or equal to 0.5

micron with an aspect ratio of 5:1 or greater with substantially parallel

sides.

Bundle: is a structure composed of three or more fibers in parallel arrangement,

with each fiber closer than the diameter of one fiber.

Cluster: is a structure with fibers in random arrangements such that all fibers are

intermixed and no single fiber is isolated from the group.

Matrix: is a fiber or fibers with one end free and the other end embedded or

hidden by a particulate. The exposed fiber end must meet the fiber

definition given above.

If more than 50 asbestos structures are identified and confirmed on a sample, AHERA analysis may be terminated after completion of the grid opening, which contains the 50th structure. AHERA protocol requires the laboratory to reject any clearance sample which contains in excess of 25% total particulate loading or which appears to be unevenly loaded.

The AHERA protocol includes specific sampling requirements, including minimum numbers of samples and minimum air volumes. Specifically, the 70 structures/mm² clearance criteria is only allowed for sets five inside samples (collected in a group of 13 samples including: five outsides and three blanks) with volumes greater than 1200 liters (40 CFR Part 763, page 41894). Deviation from the AHERA sampling protocol may affect the validity of the analytical results. Analysis of samples collected by non-protocol methods are not accredited by NVLAP

Equations Used for Calculations

Area Analyzed, mm² = # GO counted x Average GO Area (mm)

Concentration, $s/cc = \frac{\text{\# Asbestos Structures}}{\text{\# GO Counted}} \times \frac{1}{\text{Volume (L)}} \times \frac{\text{Eff Filter Area (mm}^2)}{\text{Average GO area (mm}^2)} \times \frac{1L}{1000cc}$

Filter loading, s/mm² = # Asbestos structures Area Analyzed (mm²)

GO = TEM grid opening